



Two-way C&I Gas Metering for Utility Efficiency

The M225 C&I Gas Communications Module provides a two-way AMI communications retrofit solution for large diaphragm gas meters over Landis+Gyr's scalable, secure, and interoperable Gridstream® Connect network.

The next generation solution in the widely deployed M220 product line, the M225 gas module automatically self-registers on the Gridstream Connect network upon installation, simplifying deployment by eliminating the need for field installation, configuration, and specialized tools. The module is designed to record and communicate both total consumption and two channels of interval data (configurable to intervals of 5, 15, 30 and 60 minutes), and can be configured to record and transmit data at different frequencies. This data equips utilities to develop flexible rate offerings and assists with capacity planning.

The M225 can read a wide range of makes and models of large diaphragm meters, and mounts on almost any large diaphragm gas meter built since the 1950's. The module leverages AMI connectivity through other Landis+Gyr products, such as electric meters, routers, street light controllers, or radios on distribution automation devices. This flexibility is key for maximizing the benefits of Gridstream Connect, enabling utilities to effectively manage multiple types of endpoints on a single network.

FEATURES:

- Leverages full potential and scalability of Gridstream Connect AMI network
- Patented latch counting method using a Hall Effect sensor to deliver unmatched accuracy
- Supports Landis+Gyr RF Mesh, Mesh IP, and Wi-SUN networks
- Configurable interval lengths: 5, 15, 30 and 60 minutes
- Advanced security encryption
- No field programming or special field tools required
- Performs self-diagnostics for network connectivity and firmware rollbacks
- Variety of configurable alert settings to inform of module issues such as low battery, magnetic tamper detection, tilt, stale register, extreme temperature conditions, index cover removal, cut cable detection, etc.



SCALABLE
AMI
NETWORK



ADVANCED
SECURITY
ENCRYPTION



EVENT
MONITORING



LOAD
PROFILE
DATA

PRODUCT SPECIFICATIONS

Battery Life	20-year battery life with a field-replaceable battery pack
Environmental Temperature Rating	-40°C to +85°C
Environmental Relative humidity	0% to 95%
Radio Compliances	FCC Part 15.247
Frequency Range	Radio Bandwidth 902 Mhz to 928 Mhz
ANSI Standards	ANSI B109.1, B109.2 Compliant
Intrinsic Safety	Class I Div 1 Group D
Configurable Data Transmission Options	Once every 1h, 2h, 4h, 8h, 12h or 24 hours
Sensor Interface Telemetry	2 Counting Channels + 1 Alarm Channel
Counting Telemetry Type	Form A or Form C
Alarm Telemetry Type	Form A or Form B
Output Power	Normal operation at 24 dBm with auto switch to 27 dBm as needed

COMPATIBILITY

Gas Meter Pulsar available for large diaphragm index meters from Elster, Itron, Sensus, and Schlumberger.

Pulse input cables available to use with pulse output devices from Dresser, Romet, Eagle, Mercury, and Honeywell.

This information is provided on an "as is" basis and does not imply any kind of guarantee or warranty, express or implied. Changes may be made to this information.

GET IN TOUCH

For more information and nationwide warranty terms, visit us at LandisGyr.com or call at 888-390-5733.



LET'S BUILD A BRIGHTER FUTURE TOGETHER

Since 1896, Landis+Gyr has been a global leader of energy management solutions. We've provided more than 3,500 utility companies all over the world with the broadest portfolio of products and services in the industry. With a worldwide team of 1,300+ engineers and research professionals, as well as an ISO certification for quality and environmental processes, we are committed to improving energy efficiency, streamlining operations, and improving customer service for utility providers.