

# Residential **PLX** Solution

## Full Two-Way Constant Communication for Gridstream® PLX Residential Metering

The advantages of power line carrier technology for advanced metering are fully realized in the Gridstream PLX network. The PLX residential endpoint takes full advantage of this next generation Gridstream platform to deliver a big boost in data delivery and processing power.

With the capacity and data throughput to support future smart grid applications, PLX endpoints are also easily installed as plug 'n play devices that are securely deployed through Gridstream head-end software, Command Center. The endpoints deliver 15-minute kWh or voltage intervals every 15-minutes for immediate use by the utility for smart grid applications that drive efficiency, reliability and revenue protection.

In addition to interval data, Gridstream PLX is continuously pushing full register meter reads for accurate, timely billing of energy and demand. This information is to alert the utility of abnormal consumption patterns. Outage management is improved with unsolicited alerts and restoration confirmation from each meter. Utilities are also able to improve cash flow by implementing prepay solutions and managing disconnects and reconnects remotely.

Gridstream PLX delivers updated metrology reads several times each day and diagnostics such as IEEE reliability indices and voltage sags and swells for more accurate reporting. The 15-minute interval consumption reads can also be used for engaging consumers in energy management through energy portals and consumer energy management applications.

## FOCUS AL FOCUS AX/AX-SD

### Key Benefits:

- 15-minute intervals of kWh or voltage continuously from every endpoint
- 45 days of storage of interval data at the endpoint
- Daily minimum, maximum and average voltage reads with time of occurrence by phase
- Remote control of four time-of-use rates within multiple schedules and holiday rates
- Automatic and immediate notification of meter tamper
- Remote reflashing capability to avoid obsolescence of module firmware
- Remote disconnect/connect with FOCUS AX-SD



**Landis  
+Gyr**  
manage energy better

**Specifications**

Part Number	FOCUS AL – 26-7100	
	FOCUS AX/AX-SD – 26-7200	
Operating Temperature	-40° to +85°C (under Meter Cover)	
Operating Voltage	85–264 VAC	
Setup Method	Laptop, handheld PC or remote	
<b>Compatibility</b>	Form	Voltage
	1S	CL100, 120v
	2S	CL100, 240v
	2SE	CL320, 240v
	3S	CL20, 120/240v
	4S	CL20, 240v
	12S/25S	CL200, 120v



**FOCUS AL**



**FOCUS AX-SD**

**Standards Compliance**

ANSI/IPC-A-610	Acceptability of Electronic Assemblies
FCC CFR Title 47 (Part 15,subpart B)	Radiated and Conducted Emissions
IEC 61000-4-2, IEEE C62.38-1994	Electrostatic Discharge
IEC 61000-4-3	Radiated and EMF Field Immunity
IEC 61000-4-4 2004	Electrical Fast Transient
IEC 61000-4-5, IEEE c62.41.2-2002, Category B	Surge (combination wave)
IEC 61000-4-8	Power Frequency Magnetic Field
IEC 61000-4-9	Pulsed Magnetic Field
IEC 61000-4-11	Voltage Dips and Interrupts
IEC 61000-4-12, IEEE c37.90-2002	Surge (100 kHz Ring Wave)
ANSI C12.7-1987	Code for Electricity Metering
ANSI C12.1-1995	American National Standard requirements for Watt-hour Meter Sockets

30000 Mill Creek Ave., Suite 100  
 Alpharetta, GA 30022 U.S.A  
 Phone: **678.258.1500** • FAX: **678.258.1550**  
 www.landisgyr.com

